

SIM7070G

CAT-M&NB-IoT Module







NB-IoT R14 CAT-M R14

GNSS

LWM2M/CO AP/MQTT LCC

TCP/UDP

HTTP/SSL

FOTA

Product Description

The SIM7070G is Multi-Band CAT-M, NB-IoT and GPRS module solution in a SMT type.

It has strong extension capability with rich interfaces including UART, GPIO, PCM, SPI, I2C etc. The module provides much flexibility and ease of integration for customer's application.

It is designed for applications that need low latency, Low throughput data communication in a variety of radio propagation conditions. Due to the unique combination of performance, security and flexibility, this module is ideally suited for M2M applications, such as metering, asset tracking, remote monitoring, E-health etc..

Key Benefits

- With Power Save Mode(PSM) and Extended
 Discontinuous Reception(eDRX), SIM7070G can extend
 battery life to 10 years.
- CAT-M, NB-IoT, GPRS triple mode
- The package of SIM7070G is compatible with SIM7000/SIM800F/SIM900

Smart machine Smart decision

Tel:86-21-31575100 simcom@simcom.com www.simcom.com



General Features

Support Bands:

CAT-M:

B1/B2/B3/B4/B5/B8/B12/B13/B14/B18/B19/B20/B25/B2

6/B27/B28/B66/B71/B85

CAT-NB:

B1/B2/B3/B4/B5/B8/B12/B13/B18/B19/B20/B25/B26/B2

8/B66/B71/B85 GSM/GPRS:

850/900/1800/1900MHz Control Via AT Commands

Supply voltage range: 3.2V-4.2V(TBD)

Operation temperature: -40°C to +85°C

Dimensions: 24 X 24 X 2.4(THICKNESS TBD) mm

Weight: TBD

GNSS

GPS, Beidou, GLONASS, Galileo

Data

Cat-M: Uplink: 1119Kbps Downlink:589Kbps NB-IoT: Uplink: 150Kbps Downlink:136Kbps

GPRS: Compatible with MCS 12

Consumption

PSM: TBD Sleep: TBD Idle: TBD eDRX: TBD

Other Features

TCP/UDP

HTTP/HTTPS/TLS/DTLS/PING/LWM2M/COAP/MQTT

Ayla Cloud

Firmware update via USB

FOTA

EAT

Interfaces

UART

SIM card

PCM/I2S

SPI

I2C

GPIO

ADC

USB

Embedded SIM (optional)

Certifications(plan)

FCC/IC/ANATEL

PTCRB

AT&T/TMOBILE/VERIZON

RoHS/REACH

Smart machine Smart decision

Tel:86-21-31575100 simcom@simcom.com www.simcom.com