

Stand Alone IP65 LCD


USB Type-C Display

7"

Specifications


RoHS
COMPLIANT
2011/65/EU

Model Name	W07L100-GC01HB-C
Panel Size	7"
Active Display Area (mm)	153.6 (H) x 90 (V)
Resolution	1024 x 600
Brightness	1000 (Typical) nits
Contrast Ratio	700:1 (Typical)
Viewing Angle (CR>=10 L/R/U/D)	-75~75(H) ; -75~70(V)
Display Colors	16.7M (8 bits/color)
Standard Input Signal	1 x USB Type-C connector
Touch Screen	Projected Capacitive Multi-touch (Default) or Protection Glass (non-touch) (Optional)
Speakers	1 x Speaker (Optional)
OSD	5 Keys: -, +, Power, Esc, Enter
Power Source	USB Type-C Alt mode (5V/3A)
Power Consumption	9W typical, Normal operation
Operating Temperature	0~50°C
Storage Temperature	-10~60 °C
Accessories (Optional)	Lockable USB-C to Standard USB-C Cable Dual-side Lockable USB-C Cable Waterproof USB-C to Lockable USB-C Cable
IP Rating	Front IP65
Certifications	CE, FCC



1. USB Type-C Connector
2. OSD Button

Mechanical Drawing




Stand Alone IP65 LCD

USB Type-C Display

Pin Assignment of Cables


USB Type-C




Pin No.	Symbols	Color
A1	GND	
A2	TX1+	Blue
A3	TX1-	White
A4	VBUS	Red
A5	CC1	Blue
A6	D+	Green
A7	D-	White
A8	SBUS1	Red
A9	VBUS	Red
A10	RX2-	White
A11	RX2+	Orange
A12	GND	

Pin No.	Symbols	Color
B1	GND	
B2	TX2+	Purple
B3	TX2-	White
B4	VBUS	Red
B5	VCONN	Yellow
B6	NC	
B7	NC	
B8	SBUS2	Black
B9	VBUS	Red
B10	RX1-	White
B11	RX1+	Yellow
B12	GND	


Lockable USB-C to Standard USB-C Cable P/N : 9480240240K5



Dual-side Lockable USB-C Cable P/N : 9480240240K6



Waterproof USB-C to Lockable USB-C Cable P/N : 9480240240K8



Distributed by:

