This is a controlled document. Check on Batam-intranet or SAP system for latest update. View A position of 2 weld points on the Scale 5:1 electrode and cup area not fixed. (Cell diameter & including overlaps tape thickness) - Twisted and lead-free tinned (2x). Crimping tags orientation *Ø12.28 ^{+0.10} -*2.0 (2x) Positive 2D barcode may be cover by tag. View without kapton tape (Including tags thickness) (Cell Height) (Tags thickness) Black (AWG 30, UL 1571) -5.6 ^{+0.3}_{-0.3}(2x) - ##5.4 ^{+0.2} Α - *0.10 ^{+0.01}_{-0.01} (2x) *0.06 (Kapton tape thk) Kapton tape overlaps upto 1mm Red (AWG 30, UL 1571) + and overlaps position is not fixed. Venting holes (3x120°) *29.8 (2x) -42.0 ^{+3.0}_{-3.0} (2x) VARTA marking orientation only for reference, these markings may be covered Sumitube F34 *(Ø1.0x4.0mm) (2x) Negative barcode do not cover by tag and the position may be varius with assembly. *Insulation tapes (2x) Approx. wt: 2.0 g 0 22-N032 Initial released (refer to preliminary drawing P26-00965 rev.100) 2022-11-08 Tholib S No AO No Revision Date Description: CP1254 A4X IP W SOC 30% with kapton and crimping tags Material . Projection: Refer to part list no: 805999 Note: 1) *Dimensions for reference only. 2) Dimensions to be considered for measurement. Dimension in mm 4 0 0 Dwg. No: 3) ##Cell deflection space needs to be considered, therefore observe CoinPower Handling Precautions 4) BATTERY VALIDATION INCLUDING SAFETY ELECTRONICS MUST 805999 2022-11-08 2022-11-08 Tholib S Tolerance : As specified Checked lan 63125 201 334 VKB Order No: : NTS 2022-11-09 Sunil S
nent, without notice. This drawing is the property of VARTA
sent of VARTA Microbatterv. Approved BE DONE BY CUSTOMER ACCORDING TO UL 2054. VARTA