

EBOX-33xxA Series

- ▶ Fanless design
- ▶ VESA mounting support
- ▶ MSTI PDX-600
- ▶ Onboard 256MB/512MB DDR2
- ▶ PXE Diskless Boot
- ▶ Compact Flash slot
- ▶ Micro SD slot
- ▶ 3 x USB V2.0 ports (2 at the front)
- ▶ 10/100 Mbps LAN
- ▶ 2 x RS-232 ports (optional)
- ▶ Mini PCI socket (optional)
- ▶ Wireless LAN (optional)
- ▶ 2.5" Hard Disk support (optional)
- ▶ Ultra low power

EBOX-33xxA Series

Specifications

| | | | | | |
|-------------------------|---|--------------|--------------|-------------------------------------|---------------|
| Model Type | EBOX-3300A | EBOX-3300A-H | EBOX-3300A-M | EBOX-3300A-JSK | EBOX-3300A-L2 |
| Processor | MSTI PDX-600 (600 MHz) | | | | |
| BIOS | AMI BIOS | | | | |
| Memory | Onboard 256MB DDR2/Onboard 512MB DDR2 (Note 1.) | | | | |
| VGA | XGI Z9s with 32MB DDR2/D-Sub 15-pin | | | | |
| Ethernet | 10/100 Mbps LAN (RJ45 connector) | | | Built-in PXE diskless boot function | |
| USB | 3 ports (2 at the front, 1 at the rear) | | | | |
| Audio | Mic in and Line out | | | | |
| Micro SD | 1x | | | | |
| Type III CF Slot | 1x | | | | |
| PS/2 for Keyboard/Mouse | 1x | | | | |
| MIO RS-232 | N/A | | | 2x | |
| Mini PCI Slot | N/A | | 1x | | N/A |
| IDE (Note 2.) | N/A | | 1x | | N/A |
| Power | +5V @ 2A (10W) | | | | |
| Dimensions | 115 x 115 x 35 mm | | | | |
| Weight | 505g | | | | |
| Operation Temp. | 5 ~ 50°C | | | | |
| Certification | CE, FCC, VCCI | | | | |

Note :

1. 512MB DDR2 version called 3310A series.
2. 2.5" Internal IDE HDD supported.

Ordering Information:

- EBOX-3300A/3310A: Standard Version
 EBOX-3300A-M/3310A-M: Standard Version with Mini PCI support
 EBOX-3300A-H/3310A-H: Standard Version with 2.5" IDE support
 EBOX-3300A-JSK/3310A-JSK: Standard Version with Mini PCI support and 2 x RS-232 ports
 EBOX-3300A-L2/3310A-L2: Standard Version with 2 x LAN and 2 x RS-232, no PS/2
 EBOX-3300A-LS/3310A-LS: Standard Version with 128MB CF card + DMP Embedded Linux OS



Distributed by:



www.texim-europe.com