



Features

- RockChip RK3568
- 2GB LPDDR4
- 32GB eMMC
- CE, FCC Class B

Distributed by:



RockChip
RK3568



2GB RAM



32GB eMMC



PCAP
Touch



Android 11

Specifications

System Information

Processor	Rockchip RK3568
System Memory	2GB LPDDR4

Storage

Storage	32GB eMMC
---------	-----------

Power Requirement

DC Input	DC 12 ~ 24V
----------	-------------

Software Support

OS	Androd 11 Debian 10
----	------------------------

Certification

Certification Information	CE, FCC Class B
---------------------------	-----------------

External I/O


External I/O Connector	1 x DC Jack 1 x Power Button 1 x Reset 1 x RS232 DB9 1 x RS485 DB9 2 x USB 3.0 Type A
------------------------	--

Mechanical & Environmental

Operating Temp.	0°C ~ 40°C (32°F ~ 104°F)
Storage Temp.	-20°C ~ 60°C (-4°F ~ 140°F)
Operating Humidity	40°C @ 95% Relative Humidity, Non-condensing
Dimension (W x L x H)	535.34 x 329.31 x 48.1 mm
Weight	7.2 kg

Distributed by www.texim-europe.com

Mechanical Drawing




Ordering Information

P/N	Touch Type	Processor	Memory	Storage	Resolution	I/O Ports (COM/USB/LAN)	Power Input	Working Temp.	OS Support
SID-21WR2-6803-A1R	PCAP	Rockchip RK3568	2GB DDR4	32GB eMMC	1920 x 1080	2/2/1	DC 12~24V	0°C ~ 40°C (32°F ~ 104°F)	Android 11

Packing List

Item	P/N	Quantity
SID-21WR2 Panel PC	SID-21W04-3411-A1R	1
AC 60W Adapter	ACC-ADP-060N-08R	1
Power Cord	E1702031000R	1
WiFi Antenna	E199TN00028R	2
Screw-Flat M4 x 4mm	ACC-SCREW-0001R	4

I/O Overview



Distributed by www.texim-europe.com

Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Texim Europe B.V. its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Texim"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Texim makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product.


It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application.

Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time.

All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts.

Please contact us if you have any questions about the contents of the datasheet.

This may not be the latest version of the datasheet. Please check with us if a later version is available.





Headquarters & Warehouse

Elektrostraat 17
NL-7483 PG Haaksbergen
The Netherlands

T: +31 (0)53 573 33 33
E: info@texim-europe.com
Homepage: www.texim-europe.com



The Netherlands

Elektrostraat 17
NL-7483 PG Haaksbergen

T: +31 (0)53 573 33 33
E: nl@texim-europe.com



Belgium

Zuiderlaan 14, box 10
B-1731 Zellik

T: +32 (0)2 462 01 00
E: belgium@texim-europe.com



UK & Ireland

St Mary's House, Church Lane
Carlton Le Moorland
Lincoln LN5 9HS

T: +44 (0)1522 789 555
E: uk@texim-europe.com



Germany

Bahnhofstrasse 92
D-25451 Quickborn

T: +49 (0)4106 627 07-0
E: germany@texim-europe.com



Germany

Martin-Kollar-Strasse 9
D-81829 München

T: +49 (0)89 436 086-0
E: muenchen@texim-europe.com



Austria

Warwitzstrasse 9
A-5020 Salzburg

T: +43 (0)662 216 026
E: austria@texim-europe.com



Nordic

Stockholmsgade 45
2100 Copenhagen

T: +45 88 20 26 30
E: nordic@texim-europe.com



Italy

Martin-Kollar-Strasse 9
D-81829 München

T: +49 (0)89 436 086-0
E: italy@texim-europe.com