

Technical Data Sheet

Power Management Module RRC-PMM240



Power Management Module for Mobile Applications

Features:

- 240 Watt max. output power to application
- 82 Watt max. output power to battery
- Automatic power source selection
- Wide DC input voltage range
- 3D data available of power management module and batteries for easy integration into user application
- Fits to standard smart batteries from RRC (e.g. RRC2020, RRC2024, RRC2040, RRC2040-2, RRC2054, RRC2057, ...)

Applications:

- Power management and smart battery charging capability for medical and industrial applications

Specification

Power supply Input

Input voltage range	Min. Battery charge voltage+1V Max. 24VDC
Total input power	192W max.
Input current	8A max.
Input fuse	12A
Protection	Reverse polarity, short current

Power Management

Automatic power source selection with seamless transition between ext. DC power supply and battery

Environmental Condition

Operating Temperature	-20° to +60°C
Transport & Storage Temperature	-20° to +60°C
Relative Humidity	5% - 95% non-condensing
Ambient pressure	500-1070hPa

Recommended Voltage for External AC/DC Power Supplies

Battery architecture	DC input voltage	Power supply wattage @ 4A max input current	Power supply wattage @ 8A max input current
1SxP	6VDC	≥30W	≥60W
2SxP	12VDC	≥48W	≥96W
3SxP	15VDC	≥64W	≥128W
4SxP	19VDC	≥80W	≥160W

Regulatory Approvals

International: IEC 60601-1(ed.3), IEC 60601-1(ed.3);am1	USA: ANSI/AAMI ES60601-1:2005/(R)2012 Canada: CAN/CSA-C22.2 NO. 60601-1:14
---	---

Mechanical Details

Board dimensions (LxWxH)	60mm x 50mm x 11mm, without cables and connectors
Weight	Typical 22g
Connectors:	DC input & DC output (2 pin) / User interface (6 pin) / Battery connector (5 pin smart battery connector)

To facilitate a fast design-in process for developers, RRC is providing 3D data of the power management module RRC-PMM240 and the battery housings of RRC smart battery. For an application note related to the power management module with additional details contact your RRC representative. For further information on the RRC smart batteries please refer to the RRC website (www.rrc-ps.com).

Germany/Headquarters

RRC power solutions GmbH
Technologiepark 1
D-66424 Homburg / Saar

Tel.: +49 6841 98090
Fax: +49 6841 9809280
Email: sales@rrc-ps.de
Web: www.rrc-ps.de

USA

RRC power solutions Inc.
18340 Yorba Linda Blvd.,
Suite 107-437
Yorba Linda, CA 92886-4104

Tel.: +1 714 777 3604
Fax: +1 714 777 3658
Email: usa@rrc-ps.com
Web: www.rrc-ps.com

Hong Kong

RRC power solutions Ltd.
S-V,6/F, Valiant Industrial Centre
2-12 Au Pui Wan Street
Fo Tan, N.T., Hong Kong
Tel.: +852 2376 0106
Fax: +852 2375 0107
Email: hkrcc@rrc-ps.cn
Web: www.rrc-ps.com

China

RRC power solutions Ltd.
Room 520, Yuanlin Building,
Aiguo Road No. 3066,
Luohu District, Shenzhen 518021
Tel.: +86 755 8374 1908
Fax: +86 755 8374 1861
Email: hkrcc@rrc-ps.cn
Web: www.rrc-ps.com

The Netherlands



Elektrostraat 17
NL-7483 PG Haaksbergen

T: +31 (0)53 573 33 33
F: +31 (0)53 573 33 30
E: nl@texim-europe.com

Belgium



Zuiderlaan 14 bus 10
B-1731 Zellik

T: +32 (0)2 462 01 00
F: +32 (0)2 462 01 25
E: belgium@texim-europe.com

UK & Ireland



St. Mary's House, Church Lane
Carlton Le Moorland
Lincoln LN5 9HS

T: +44 (0)1522 789 555
F: +44 (0)845 299 22 26
E: uk@texim-europe.com

Germany North



Bahnhofstrasse 92
D-25451 Quickborn

T: +49 (0)4106 627 07-0
F: +49 (0)4106 627 07-20
E: germany@texim-europe.com

Germany South



Martin-Kollar-Strasse 9
D-81829 München

T: +49 (0)89 436 086-0
F: +49 (0)89 436 086-19
E: germany@texim-europe.com

Austria



Warwitzstrasse 9
A-5020 Salzburg

T: +43 (0)662 216 026
F: +43 (0)662 216 026-66
E: austria@texim-europe.com

Nordic region



Sdr. Jagtvej 12
DK-2970 Hørsholm

T: +45 88 20 26 30
F: +45 88 20 26 39
E: nordic@texim-europe.com

General information



info@texim-europe.com
www.texim-europe.com