

NOVAsom M-line is a family of **SBCs** specifically developed for High end multimedia markets that require heavy **Full HD** movies or multiple **4k UHD**, that need to be managed with high fluidity without compromise in performance.

Thanks to the different architectures it's possible to chose between various OS like Linux, Android or Windows 10 and IoT.

Examples of applications are: **Digital Signage, Infotainment, multimedia and advertising.**



Distributed by:



		SBC-M7 & M7+ Boards	SBC-M8 Boards	SBC-M9 Boards	SBC-M11 Boards
Processor	CPU	Rockchip RK3328	Qualcomm Snapdragon 410E	RK3399 Dual A72 + Quad A53	Intel Apollo Lake X5 6th generation Dual or quad core
Graphic	GRAPHICS ENGINE	Mali-450MP4	ADRENO	Mali-T860MP4	Intel HD Graphics 405/505
Memory	RAM memory DDR3	Up to 2 GB	1 or 2 GB	LPDDR3 up to 4GB @ 64bit	SODIMM DDR3 up to 8GB
	eMMC flash memory	Up to 256 GB	8 or 16 GB in bundle with ram	up to 128 GB	Any size eMMC supported SDR and DDR mode
	µSD slot	Y	Y	Y	Y
Power	Power supply	12v (6.5 - 18Vcc protected) * 5V via USB (only M7+)	12v (6.5 - 18Vcc protected)	12v (6.5 - 18Vcc protected)	12v (6.5 - 18Vcc protected redundant)
	Power Consumption Active [W]	2.5	6	2.5	10-15
	UPS Manager	Y (battery not included)	Y (battery not included)	Y (battery not included)	Y (battery not included)
	PoE	N	N	N	Y + Relaunch
Multimedia	HDMI full size connector	Y * Additional FFC connector (only M7+)	Y	Y	Y
	LVDS	External adapter	n.a.	n.a.	2 ch@1920x1080
	Display Port DP 1.2 or eDP1.3	n.a.	n.a.	Y	Y
	PCAP on Connector (Dedicated I2C Channel)	1	1	1	1
	Display MIPI-DSI	n.a.	Y	Y	Y
	Camera MIPI-CSI PHY 1.1 (¹)	n.a.	Y	Y	Y
	Camera MIPI-CSI PHY 1.2	n.a.	n.a.	Y	Y
	Camera parallel	Y	n.a.	n.a.	n.a.
I/O	Audio	Y – Analog line out	Y - Analog on jack	Y - Standard 2.5mm jack	Y – High Def Audio 5
	On Board reconfigurable GPIO (¹)	22 @3.3V	22 @1.8V	26 @3.3V	26 @3.3V
	On board protected GPIO	n.a.	n.a.	n.a.	Y
USB	USB port Host/Device on TYPE - A	1xUSB 3.0 + 1xUSB 2.0	Y	2xUSB 3.0 + 2xUSB 2.0	3xUSB 3.0 + 2xUSB 2.0
	USB 2.0 OTG on micro for debug	Y	Y	Y / USB3	N
	USB 3.0 and 2.0 OTG repeated on strip	*Y (only M7+)	N	Y	N
	USB 2.0 on strip	N	N	N	Y-2
Communication	I2C	2 on strip @ 3.3 V (²)	2 on strip @ 3.3 V (²)	Y	2 on strip @3.3 (²)
	SPI	1 on strip @ 3.3 V (²)	2 on strip @ 3.3 V (²)	Y	2 on strip @ 3.3(²)
	On board SATA	n.a.	n.a.	n.a.	Y
	RS485	* Y on connector (only M7+)	N	N	N
	Console RS232	Y-TTL	Y	Y	Y
	mPCIe slot	n.a.	n.a.	n.a.	Y
	PCIe full size	n.a.	n.a.	n.a.	Y
	M2 slot	n.a.	n.a.	Y	n.a.
Networking	RJ 45 Ethernet connector on board	Y – 100 Mb	Y - Gb	Y-Gb	2 x Gb/s with dual MAC address
	WIFI and BT	WIFI 802.11 a/b/g/n with PCB antenna	WIFI 802.11 a/b/g/n with PCB antenna	WIFI 802.11 a/b/g/n/ac with PCB antenna , BLE 4.1	WIFI 802.11 a/b/g/n with PCB antenna
	GPS	N	Y	N	Any GPS available on mPCIe slot or USB
Generic	Additional user led	Y - 1	Y -5	Y - 1	Y -5
	RTC with external rechargeable battery	Y	Y	Y	Y
	User reset push-button	Y	Y	Y	Y
Dimension	Mechanical size	85 x 56 mm (¹)	85 x 56 mm (¹)	105 x 56 mm (¹)	170x170 mm
	Form factor	Credit Card	Credit Card	Credit Card extended	Mini ITX
Temperature	Operating temperature	0- ÷ 70 °C	-30 ÷ +60 °C	0 ÷ +80 °C / -20 ÷ +85 °C	-20 ÷ +70 °C / -40 ÷ +85 °C
Operating System	Distributions supported	Android, Linux, Yocto, Ubuntu, Debian, Raspbian (²)	Android 5.1/6, Linux based on Debian 8.0/Ubuntu 14, Windows 10 IoT Core (²)	Android, Linux	Windows 10, Linux (²)

NOTE: for more information please refer to Hardware User Manual.



	SBC Board code	SBC-M7/M7+ Boards				
		SBC-M7A/ SBC-M7+A	SBC-M7B/ SBC-M7+B	SBC-M7C/ SBC-M7+C	SBC-M7D/ SBC-M7+D	SBC-M7FT/ SBC-M7+FT
 Processor	CPU	Rockchip RK3328	Rockchip RK3328	Rockchip RK3328	Rockchip RK3328	Rockchip RK3328
 Graphic	GRAPHICS ENGINE	Mali-450MP4	Mali-450MP4	Mali-450MP4	Mali-450MP4	Mali-450MP4
 Memory	RAM memory DDR3	Y – 1 GB@32bit	Y – 1 GB@32bit	Y – 1 GB@32bit	Y – 2 GB@32bit	Y – 2 GB@32bit
	eMMC flash memory	N	N	N	N	16 GB
	µSD slot (card not included)	Y	Y	Y	Y	Y
 Power	Power supply	* 5V via USB (only M7+)	* 5V via USB (only M7+)	12v (6.5 - 18Vcc protected) * 5V via USB (only M7+)	12v (6.5 - 18Vcc protected) * 5V via USB (only M7+)	12v (6.5 - 18Vcc protected)
	Power Consumption [W]	2.5	2.5	2.5	2.5	2.5
	UPS MANAGER	Y - battery not included	Y - battery not included	Y - battery not included	Y - battery not included	Y - battery not included
 Multimedia	HDMI full size connector	* Additional FFC connector (only M7+)	* Additional FFC connector (only M7+)	* Additional FFC connector (only M7+)	* Additional FFC connector (only M7+)	* Additional FFC connector (only M7+)
	LVDS	External adapter	External adapter	External adapter	External adapter	External adapter
	Display Port DP 1.2 OR eDP 1.3	n.a.	n.a.	n.a.	n.a.	n.a.
	PCAP on Connector (Dedicated I2C Channel)	1	1	1	1	1
	Display MIPI-DSI	n.a.	n.a.	n.a.	n.a.	n.a.
	Camera MIPI-CSI PHY 1.1 (¹)	n.a.	n.a.	n.a.	n.a.	n.a.
	Camera MIPI-CSI PHY 1.2	n.a.	n.a.	n.a.	n.a.	n.a.
	Camera parallel	Y	Y	Y	Y	Y
 I/O	Audio	Y – Analog line out	Y – Analog line out	Y – Analog line out	Y – Analog line out	Y – Analog line out
	On Board reconfigurable GPIO (¹)	22 @3,3V	22 @3,3V	22 @3,3V	22 @3,3V	22 @3,3V
	OnBoard Protected GPIO	n.a.	n.a.	n.a.	n.a.	n.a.
 USB	USB port Host/Device on TYPE - A	1xUSB 3.0 + 1xUSB 2.0	1xUSB 3.0 + 1xUSB 2.0	1xUSB 3.0 + 1xUSB 2.0	1xUSB 3.0 + 1xUSB 2.0	1xUSB 3.0 + 1xUSB 2.0
	USB 2.0 OTG on micro for debug	Y	Y	Y	Y	Y
	USB 3.0 and 2.0 OTG repeated on strip	* Y (only M7+)	* Y (only M7+)	* Y (only M7+)	* Y (only M7+)	* Y (only M7+)
	USB 2.0 on strip	N	N	N	N	N
 Communication	I2C	2 on strip @ 3.3 V (²)	2 on strip @ 3.3 V (²)	2 on strip @ 3.3 V (²)	2 on strip @ 3.3 V (²)	2 on strip @ 3.3 V (²)
	SPI	1 on strip @ 3.3 V (²)	1 on strip @ 3.3 V (²)	1 on strip @ 3.3 V (²)	1 on strip @ 3.3 V (²)	1 on strip @ 3.3 V (²)
	On board SATA	n.a.	n.a.	n.a.	n.a.	n.a.
	RS485	N	N	N	N	* Y on connector (only M7+)
	Console RS232	Y-TTL	Y-TTL	Y-TTL	Y-TTL	Y-TTL
	mPCIe slot	n.a.	n.a.	n.a.	n.a.	n.a.
	PCIe full size	n.a.	n.a.	n.a.	n.a.	n.a.
 Networking	RJ 45 Ethernet	1 x 100 Mb/s	1 x 100 Mb/s	1 x 100 Mb/s	1 x 100 Mb/s	1 x 100 Mb/s
	WIFI and BT	N	WIFI 802.11 a/b/g/n with PCB antenna	WIFI 802.11 a/b/g/n with PCB antenna	WIFI 802.11 a/b/g/n with PCB antenna	WIFI 802.11 a/b/g/n with PCB antenna
	GPS	N	N	N	N	N
 Generic	Additional user led	Y-1	Y-1	Y-1	Y-1	Y-1
	RTC with external rechargeable battery	Y	Y	Y	Y	Y
	User reset push-button	Y	Y	Y	Y	Y
 Dimension	Mechanical size	85 x 56 mm (¹)	85 x 56 mm (¹)	85 x 56 mm (¹)	85 x 56 mm (¹)	85 x 56 mm (¹)
	Form factor	Credit Card	Credit Card	Credit Card	Credit Card	Credit Card
 Temperature	Operating temperature	0- ÷ 70 °C	0- ÷ 70 °C	0- ÷ 70 °C	0- ÷ 70 °C	0- ÷ 70 °C / -20 ÷ +85 °C
 Operating System	Distributions supported	Android, Linux, Yocto, Ubuntu, Debian, Raspbian (³)	Android, Linux, Yocto, Ubuntu, Debian, Raspbian (³)	Android, Linux, Yocto, Ubuntu, Debian, Raspbian (³)	Android, Linux, Yocto, Ubuntu, Debian, Raspbian (³)	Android, Linux, Yocto, Ubuntu, Debian, Raspbian (³)



(¹) RASPMOOD : form factor , mechanical holes , expansion pin on strip , connector kind and position same of famous Pi Family

(²) Strip NOT mounted (2.54), to leave customer free for any choice

(³) Detailed info on SW and SW versions are in the Software menu of www.novasomindustries.com/

* This means only on M7 Plus

NOTE: OPTIONS are related to the Tailor Made solutions. You choose the CPU than the options you need and you have your Tailor Made board.



		SBC-M8 Boards			SBC-M9 Boards			SBC-M11 Boards
		SBC Board code	SBC-M8A	SBC-M8FT	SBC-M9D	SBC-M9E	SBC-M9FT	SBC-M11FT
	Processor	CPU	Qualcomm Snapdragon 410E	Qualcomm Snapdragon 410E	RK3399 Dual A72 + Quad A53	RK3399 Dual A72 + Quad A53	RK3399 Dual A72 + Quad A53	Intel Apollo Lake N42
	Graphic	GRAPHICS ENGINE	ADRENO 405	ADRENO 405	Mali-T860MP4	Mali-T860MP4	Mali-T860MP4	Intel HD 405 / 505
	Memory	RAM memory DDR3	Y – 1 GB@16bit	Y – 1 GB@16bit	Y – 2 GB@64 bit	Y – 2 GB@64 bit	Y – 4 GB@64 bit	SODIMM x2 slot up to 8GB @64bit
		eMMC flash memory	8 GB	8 GB	N	64 GB	64 GB	16 GB
		µSD slot (card not included)	Y	Y	Y	Y	Y	Y
	Power	Power supply	12v (6.5 - 18Vcc protected)	12v (6.5 - 18Vcc protected)	12v (6.5 - 18Vcc protected)	12v (6.5 - 18Vcc protected)	12v (6.5 - 18Vcc protected)	12v (6.5 - 18Vcc protected redundant)
		Power Consumption [W]	6	6	2.5	2.5	2.5	10-15W
		UPS MANAGER	Y - battery not included	Y - battery not included	Y (battery not included)	Y (battery not included)	Y (battery not included)	Y - battery not included
		PoE	N	N	N	N	N	Y + Relaunch
	Multimedia	HDMI full size connector	n.a.	Y	Y	Y	Y	Y – 4k
		LVDS	n.a.	n.a.	n.a.	n.a.	n.a.	LVDS 2ch@1920x1080
		Display Port DP 1.2 OR eDP 1.3	n.a.	n.a.	Y	Y	Y	Y - 4k with audio
		PCAP on Connector (Dedicated I2C Channel)	1	1	1	1	1	1
		Display MIPI-DSI	1ch 1920x1080 (x4 lane) 1920x1080 @ 60 Hz	1ch 1920x1080 (x4 lane) 1920x1080 @ 60 Hz	Y	Y	Y	1 ch 1920x1080 @ 60 Hz (x4 lane) OR 1 ch 2560x1600 @ 60 Hz (2x4 lane)
		Camera MIPI-CSI PHY 1.1 (¹)	2 ch 1920x1080 (x4 lane)	2 ch 1920x1080 (x4 lane)	Y	Y	Y	1 ch 1920x1080 (x4 lane) OR 1 ch @4k (2x4 lane)
		Camera MIPI-CSI PHY 1.2	n.a.	n.a.	Y	Y	Y	1 ch 1920x1080 (x4 lane) OR 1 ch @4k (2x4 lane)
		Camera parallel	n.a.	n.a.	n.a.	n.a.	n.a.	n.a.
	I/O	Audio	Y - PCM on strip @ 1.8 V (²)	Y - PCM on strip @ 1.8 V (²)	Y - Standard 2.5mm jack	Y - Standard 2.5mm jack	Y - Standard 2.5mm jack	High Definition Audio 5+1 Spdif
		On Board reconfigurable GPIO (¹)	22 @1.8V	22 @1.8V	26 @3.3V	26 @3.3V	26 @3.3V	26 @3.3V
		OnBoard Protected GPIO	n.a.	n.a.	n.a.	n.a.	n.a.	2 O.C. out up to 30V, 2 in up to 30V
	USB	USB 2.0 port Host/Device on TYPE A	N	1 USB	2xUSB 3.0 + 2xUSB 2.0	2xUSB 3.0 + 2xUSB 2.0	2xUSB 3.0 + 2xUSB 2.0	3X USB 3.0; 2 x USB2.0
		USB 2.0 OTG on micro for debug	Y	Y	Y / USB3	Y / USB3	Y / USB3	N
		USB 3.0 and 2.0 OTG rep. on strip	N	N	Y	Y	Y	N
		USB 2.0 on strip	N	N	N	N	N	Y – 2
	Communication	I2C	2 on strip @ 3.3 V (²)	2 on strip @ 3.3 V (²)	Y	Y	Y	2 on strip @ 3.3V (²)
		SPI	2 on strip @ 3.3 V (²)	2 on strip @ 3.3 V (²)	Y	Y	Y	1 on strip @ 3.3V (²)
		On board SATA	n.a.	n.a.	n.a.	n.a.	n.a.	Y - 2 x SATA III
		RS485	N	N	N	N	N	N
		Console RS232	Y	Y	Y	Y	Y	Y
		mPCIe slot	n.a.	n.a.	n.a.	n.a.	n.a.	3 (2 full + 1 only usb and sim)
		PCIe full size	n.a.	n.a.	n.a.	n.a.	n.a.	1 (full 2 lane)
		M2 slot	n.a.	n.a.	Y	Y	Y	n.a.
	Networking	RJ 45 Ethernet	N	1 x Gb/s	Y	Y	Y	2 x Gb/s with dual MAC address
		WIFI and BT	N	WIFI 802.11 a/b/g/n with PCB antenna	WIFI 802.11 a/b/g/n/ac with PCB antenna , BLE 4.1	WIFI 802.11 a/b/g/n/ac with PCB antenna , BLE 4.1	WIFI 802.11 a/b/g/n/ac with PCB antenna , BLE 4.1	WIFI 802.11 a/b/g/n with PCB antenna
		GPS	N	N	N	N	N	On mPCIe slot or USB
	Generic	Additional user led	Y - 5	Y - 5	1	1	1	Y – 5
		RTC with external recharg. battery	N	Y	Y	Y	Y	Y
		User reset push-button	Y	Y	Y	Y	Y	Y
	Dimension	Mechanical size	85 x 56 mm (¹)	85 x 56 mm (¹)	105 x 56 mm (¹)	105 x 56 mm (¹)	105 x 56 mm (¹)	170 x 170 mm
		Form factor	Credit Card	Credit Card	Credit Card	Credit Card	Credit Card	Mini ITX
	Temperature	Operating temperature (ext.temp. range includes conformal coating)	-30 ÷ +60 °C	-30 ÷ +60 °C	0 ÷ +80 °C / -20 ÷ +85 °C	0 ÷ +80 °C / -20 ÷ +85 °C	0 ÷ +80 °C / -20 ÷ +85 °C	-20 ÷ +70 °C / -40 ÷ +85 °C
	Operating System	Distributions supported	Android 5.1/6, Linux based on Debian 8.0/Ubuntu 14, Windows 10 IoT Core (²)	Android 5.1/6, Linux based on Debian 8.0/Ubuntu 14, Win 10 IoT Core (²)	Android, Linux	Android, Linux	Android, Linux	Windows 10, Linux (²)

(¹) RASPMOOD : form factor , mechanical holes , expansion pin on strip , connector kind and position same of famous Pi Family

(²) Strip NOT mounted (2.54), to leave customer free for any choice

(³) Detailed info on SW and SW versions are in the Software menu of www.novasomindustries.com/

NOTE: OPTIONS are related to the Tailor Made solutions. You choose the CPU than the options you need and you have your Tailor Made board.

The Netherlands



Elektrostraat 17
NL-7483 PG Haaksbergen

T: +31 (0)53 573 33 33
F: +31 (0)53 573 33 30
E: nl@texim-europe.com

Belgium



Zuiderlaan 14 bus 10
B-1731 Zellik

T: +32 (0)2 462 01 00
F: +32 (0)2 462 01 25
E: belgium@texim-europe.com

UK & Ireland



St. Mary's House, Church Lane
Carlton Le Moorland
Lincoln LN5 9HS

T: +44 (0)1522 789 555
F: +44 (0)845 299 22 26
E: uk@texim-europe.com

Nordic region



Sdr. Jagtvej 12
DK-2970 Hørsholm

T: +45 88 20 26 30
F: +45 88 20 26 39
E: nordic@texim-europe.com

Germany North



Bahnhofstrasse 92
D-25451 Quickborn

T: +49 (0)4106 627 07-0
F: +49 (0)4106 627 07-20
E: germany@texim-europe.com

Germany South



Martin-Kollar-Strasse 9
D-81829 München

T: +49 (0)89 436 086-0
F: +49 (0)89 436 086-19
E: germany@texim-europe.com

Austria



Warwitzstrasse 9
A-5020 Salzburg

T: +43 (0)662 216 026
F: +43 (0)662 216 026-66
E: austria@texim-europe.com

Italy



Via Matteotti 43
IT-20864 Agrate Brianza (MB)

T: +39 (0)39 971 3293
F: +39 (0)39 971 3293
E: italy@texim-europe.com