

Distributed by:



[www.texim-europe.com](http://www.texim-europe.com)



## Key Features

- 11.6" HD (1920 x 1080) Sunlight Readable Display
- Intel® Skylake U-series SoC
- 4GB DDR3L (x 1 SO-DIMM Socket, up to 8 GB)
- One M.2 for SSD, 64GB by Default
- Projective Capacitive Multi-Touch Panel
- Two Hot-swappable Batteries, 14.8V/ 2200mAh/ 2.2A
- MIL-STD-810G, IP65 Compliant, Drop 120cm
- 10/100/1000 Base-T Ethernet & RS-232 COM Port
- USB3.0 x 1 (Standard Connector), USB2.0 x 2 (Standard Connector)
- Programmable Function Key: Windows, Volume Up/Down with LED
- Kensington Lock Hole x 1
- Docking Connector with Pass-through ANT GNSS/WWAN
- 1D/2D Barcode Scanner (Optional)
- Windows® 10 IOT Enterprise (optional Windows® 8.1 Industry Pro)

**MIL-STD  
810G**

**IP65**



Heat & cold resistant, shock & drop resistant  
and water resistant up to IP65

## The ultimate mobile HMI

The RTC-1200SK is one of the most complete rugged tablet computers in today's market. With its various I/O's on board and optional barcode scanner as well as the fact that has been designed with customization in mind, this 11.6" work horse will fit your exact needs.



## Why RTC Tablets




Shockproof



IP 65 Certified



Turnkey extensions



Changeable battery



Military grade quality



## Technical specifications

### System

Processor	Intel® Skylake U-series Celeron, Core i3, i5 or i7
Memory & Storage I/O	One DDR3L SO-DIMM Socket, up to 8GB DC-in Jack x 1, USB 3.0 x 1, USB 2.0 x 2, RJ45 x 1, COM x 1, HDMI x1, Micro SD Card Slot x 1, 3.5-mm stereo headphone jack x 1, Built-in Speaker & Microphone, SIM Card Slot x 1
Communication WWAN (optional)	Bluetooth v4.0+EDR, Wi-Fi (802.11 a/b/g/n), 3G (Optional)
GNSS	3G: WCDMA/CDMA, LTE: HSPA+/CDMA(North America, EU) GPS, GLONASS, A-GPS. *A-GPS only available when the 3G module is enabled.
Camera	2 MP front camera, 5 MP rear camera with flash
Sensors	Light Sensor, Accelerometer, Gyroscope, E-Compass
OS	Windows 10 IOT Enterprise (optional Windows® 8.1 Industry Pro)
BCR (optional)	1D Scanner support CMOS engine, 2D Scanner support LED engine

### Environmental

Operating Temperature	-20°C to 60°C
Storage Temperature	-55°C to 70°C
Water & Dust proof	IP65 Compliance
Vibration	Meet Mil Std 810G-514.6, Procedure I ASTM 4169-99 Truck Assurance Level II, Schedule E
Drop	Mil-STD-810G-516.6, Procedure IV
Water & Dust Proof	IP65
ESD	Air +/- 16KV, Contact +/- 8KV
EMI/Safety	CE / FCC Class B / UL

### Mechanical

Color	Dark-Grey
Dimension (W x H x D)	310.4 x 200 x 24.5 mm
Gross Weight	1500g

### Power Supply

AC/DC Adapter	AC input 100V-240V, 50Hz-60Hz; DC output: 19V, 3.42A
Battery	Two Hot-swappable Batteries, 14.8V/ 2200mAh/ 2.2A for use up to 8 hours

### LCD

Display	11.6" TFT-LCD / 16:9
Resolution	1920 x 1080 Pixels
Brightness	300 or 1000 nits
Viewing angle	Vertical/ Horizontal 178°

### Touch Screen

Touch Screen	Projected Capacitive Multi-Touch panel
Light Transmission	≥ 87%

Distributed by:



For more information about our rugged tablet solutions, please contact us now!

- ☎ +31 (0) 499 745 200
- ✉ info@RTC-Tablet.com
- 🌐 www.RTC-Tablet.com

## The Netherlands



Elektrostraat 17  
NL-7483 PG Haaksbergen

T: +31 (0)53 573 33 33  
F: +31 (0)53 573 33 30  
E: [nl@texim-europe.com](mailto:nl@texim-europe.com)

## Belgium



Zuiderlaan 14 bus 10  
B-1731 Zellik

T: +32 (0)2 462 01 00  
F: +32 (0)2 462 01 25  
E: [belgium@texim-europe.com](mailto:belgium@texim-europe.com)

## UK & Ireland



St. Mary's House, Church Lane  
Carlton Le Moorland  
Lincoln LN5 9HS

T: +44 (0)1522 789 555  
F: +44 (0)845 299 22 26  
E: [uk@texim-europe.com](mailto:uk@texim-europe.com)

## Germany North



Bahnhofstrasse 92  
D-25451 Quickborn

T: +49 (0)4106 627 07-0  
F: +49 (0)4106 627 07-20  
E: [germany@texim-europe.com](mailto:germany@texim-europe.com)

## Germany South



Martin-Kollar-Strasse 9  
D-81829 München

T: +49 (0)89 436 086-0  
F: +49 (0)89 436 086-19  
E: [germany@texim-europe.com](mailto:germany@texim-europe.com)

## Austria



Warwitzstrasse 9  
A-5020 Salzburg

T: +43 (0)662 216 026  
F: +43 (0)662 216 026-66  
E: [austria@texim-europe.com](mailto:austria@texim-europe.com)

## Nordic region



Sdr. Jagtvej 12  
DK-2970 Hørsholm

T: +45 88 20 26 30  
F: +45 88 20 26 39  
E: [nordic@texim-europe.com](mailto:nordic@texim-europe.com)

## General information



[info@texim-europe.com](mailto:info@texim-europe.com)  
[www.texim-europe.com](http://www.texim-europe.com)