



OFT-15WR1

15.6" Open Frame Tablet with RK3288

- > RockChip RK3288W Cortex-A17 Quad Core 1.6GHz
- > 2GB RAM
- > 16GB eMMC
- > PCAP Touch
- > 10/100/1000 Ethernet
- > M.2 B-Key(3042) connector socket
- > 802.11 b/g/n Wireless LAN and Bluetooth 4.0
- > DC 12~24V Input
- > G sensor
- > OS Image support Android 8.1

+ Spec

System Information

Processor	RockChip RK3288W Cortex-A17 Quad Core 1.6GHz
System Memory	2GB DDR3L RAM

Storage

Storage	16GB eMMC
----------------	-----------

Panel

LCD Size	15.6"
LCD Panel	TFT-LCD
Resolution	1920x1080
Pixel pitch	179.25(H) X 179.25(V) mm
Luminance	220 cd/m2(typ)
Contrast ratio	800
Viewing angle	85 (U), 85 (D), 85 (L), 85 (R)
Response time	30 ms
Backlight	LED
Touch Type	Projective Capacitive
Touch Light Transmission	85%

I/O

External I/O Connector	1 x Power Jack 1 x HDMI Port 2 x USB Type A Host 1 x RJ45 1 x Headphone Jack 1 x Reset
Internal I/O Connector	1 x Micro USB 1 x USB interface , 1 x DMIC interface 1 x USB touch interface 1 x M.2 B-Key(3042) 1 x touch button control(power/vol/brightness) 1 x Power interface (12~24V) 1 x JLVDS1 1 x eDP 1 x AMIC interface 1 x Speaker interface 1 x JSEN1 interface (I2C x2) 1 x JITP1 interface 1 x Debug port 1 x RS232 interface 1 x RS232 , RS485 1 x JGPIO1 (GPIO 16bit) 1 x RTC Battery interface 1 x Micro SIM Card socket for LTE module 1 x Micro SD slot

Wireless Communication

WLAN	802.11 b/g/n
-------------	--------------

Display

Multiple Display	eDP+HDMI
-------------------------	----------

Certifications

Certification Information	CE, FCC Class A
----------------------------------	-----------------

Mechanical & Environmental



Operating Temperature	0°C ~ 40°C
Storage Temperature	-20°C ~ 60°C
Operating Humidity	40°C @ 95% Relative Humidity, Non-condensing
Dimension (W x L x H)	387 x 235 x 35.3mm
Weight	1.5kg
Power Requirement	DC 12~24V Input
Power Mode	DC Jack, DC input 4pin header
Software Support	
OS Information	Android 8.1
Ordering Information	
Ordering Information	OFT-15WR1-DC in