




Functional characteristics

Dimensional class:	low
Standard colour:	green
Pitches:	metric 3.5 mm, 7 mm (.138 in, .276 in) imperial 3.81 mm, 7.62 mm (.150 in, .300 in)
Stripping length:	10.5 ÷ 11.5 mm (.41 ÷ .45 in)
Operating temperature range:	-40 °C ÷ +65 °C (-40 °F ÷ +149 °F)
Contact resistance:	<15 mΩ
Insulation resistance:	>10 ⁹ Ω (500V DC)
Insulating material group:	I (CTI ≥ 600V)

Certifications

UL (n. E167473)
300 V - 11 A - 30÷14 AWG stranded (9 A - 30÷14 AWG solid) for 3.5, 3.81, 7, 7.62 mm pitch



Data according to

IEC EN 61984
150 V - 8 A - T110 - 1.5 mm² - for 3.5 mm and 3.81 mm pitch
300 V - 8 A - T110 - 1.5 mm² - for 7 mm and 7.62 mm pitch

Application values for end-use equipment have to be in accordance to norms and applicable to it.
The certifications of some product's versions could be pending, for more detailed and updated data please refer to our web site www.sauro.net or your representative Sales Manager


Please see "CONNECTORS COMBINATIONS"

Your drawings and notes




Right side stackable female

CBF_OR8 - 2 ÷ 25 poles, 3.5 mm / .138" pitch
CBF_OR9 - 2 ÷ 13 poles, 7 mm / .276" pitch
CBF_ORT - 2 ÷ 25 poles, 3.81 mm / .150" pitch
CBF_OR7 - 2 ÷ 13 poles, 7.62 mm / .300" pitch




Right locking screw flanges female

CBF_OD8 - 2 ÷ 23 poles, 3.5 mm / .138" pitch
CBF_OD9 - 2 ÷ 12 poles, 7 mm / .276" pitch
CBF_ODT - 2 ÷ 23 poles, 3.81 mm / .150" pitch
CBF_OD7 - 2 ÷ 12 poles, 7.62 mm / .300" pitch



Left side stackable female

CBF_OL8 - 2 ÷ 23 poles, 3.5 mm / .138" pitch
CBF_OL9 - 2 ÷ 13 poles, 7 mm / .276" pitch
CBF_OLT - 2 ÷ 25 poles, 3.81 mm / .150" pitch
CBF_OL7 - 2 ÷ 13 poles, 7.62 mm / .300" pitch



Left locking screw flanges female

CBF_OS8 - 2 ÷ 23 poles, 3.5 mm / .138" pitch
CBF_OS9 - 2 ÷ 12 poles, 7 mm / .276" pitch
CBF_OST - 2 ÷ 23 poles, 3.81 mm / .150" pitch
CBF_OS7 - 2 ÷ 12 poles, 7.62 mm / .300" pitch

Distributed by:



Usable with:

CTM

Page 62

CTMH


Page 64

CTM/CTMH D.

Page 66

CKF-SC1

Page 84



The Netherlands



Elektrostraat 17
NL-7483 PG Haaksbergen

T: +31 (0)53 573 33 33
F: +31 (0)53 573 33 30
E: nl@texim-europe.com

Belgium



Zuiderlaan 14 bus 10
B-1731 Zellik

T: +32 (0)2 462 01 00
F: +32 (0)2 462 01 25
E: belgium@texim-europe.com

UK & Ireland



St. Mary's House, Church Lane
Carlton Le Moorland
Lincoln LN5 9HS

T: +44 (0)1522 789 555
F: +44 (0)845 299 22 26
E: uk@texim-europe.com

Germany North



Bahnhofstrasse 92
D-25451 Quickborn

T: +49 (0)4106 627 07-0
F: +49 (0)4106 627 07-20
E: germany@texim-europe.com

Germany South



Martin-Kollar-Strasse 9
D-81829 München

T: +49 (0)89 436 086-0
F: +49 (0)89 436 086-19
E: germany@texim-europe.com

Austria



Warwitzstrasse 9
A-5020 Salzburg

T: +43 (0)662 216 026
F: +43 (0)662 216 026-66
E: austria@texim-europe.com

Nordic region



Sdr. Jagtvej 12
DK-2970 Hørsholm

T: +45 88 20 26 30
F: +45 88 20 26 39
E: nordic@texim-europe.com

Italy



Via Matteotti 43
IT-20864 Agrate Brianza (MB)

T: +39 (0)39 971 3293
F: +39 (0)39 971 3293
E: italy@texim-europe.com

General information



info@texim-europe.com
www.texim-europe.com