### CUSTOMER PRODUCT SPECIFICATION SHEET

RoHS Compliant

Patent Pending

GB2416077.2

CAB613RF: SMA SEALED PLUG TO SMA SEALED PLUG, BOTH BRASS, IP68/69K, ALSR-100 CABLE, 6GHz

### SPECIFICATIONS :


- 1. BRASS SMA SEALED PLUG, RATED TO IP68/69K, P/N: RFCT-SMA111-B-M-ALS-S (W/SILICONE GASKET).
- 2. COAXIAL CABLE, ALSR-100\*, COLOR: BLACK. (SPECIFICATION EQUIVALENT TO LMR-100®)

### ENVIRONMENTAL:

- A. SMA SEALED PLUG TESTED TO THE FOLLOWING SPECIFICATION:
- i. IP6X DUST TIGHT NO PARTICLE INGRESS.
- ii. IPX8 WATERPROOF FOR 48 HOURS AT 1 METER UNDERWATER.
- iii. IPX9K WATER SPRAY, 14-16L PER MINUTE, AT 8,000 ~ 10,000 KPA, AT 100-150MM DISTANCE FOR 30 SECONDS.

### NOTES:

- 1. WORKING FREQUENCY RANGE: DC-6GHz.
- 2. OPERATING TEMPERATURE: -40°C TO +85°C.
- 3. IMPEDANCE: 50 Ohm.




eg: 500MM = 0500 MIN. 0050, MAX. 5000.

STANDARD = 0152<mark>(6</mark>-inch), 0304(12-inch), 060<mark>9(</mark>24-inch),

0914(36-inch)

Tolerance: 50mm: ±2mm.

51-200mm: ±5mm. 201-500mm: ±7mm. 501-999mm: ±10mm. ≥1000mm: + (L x 0.02)mm GB2416078.0



SMA PLUG DETAIL DRAWING

# IP RATED EVEN WHEN UNMATED INC. CABLE ENTRY SIDE

### Distributed by: Texim Europe

### exim Europe www.texim-europe.com

REV. DATE & DRN	1.0 28/03/"24 - CC RELEASE	1.1 11/06/"24 - CC	Add note 'Patent Pending'	1.2 26/08/"24 - CC	Change cable to ALSR-100.	Change frequency to 6GHz.	Change max. cable length to 5m.	Change operating temperature to	-40°C~+85°C.	1.3 11/09/′24 - CC	Add GCT logo.	1.4 17/12/'24 - CC	Add patent numbers.	
쀭	유	∓	Ŗ	1.2	£	ŝ	£	ŝ	7	1.3	Ą	🏥	₹	



7.	iiii Eu	rope	www.texim-et							
	Scale: NTS		THIRD ANGLE			Instated .X .XX	Tolerances: ±0.2 ±0.1			
	Drawn:	СС	$\Rightarrow$	-		.XXX ANGLES	±0.05 ±1°	1		
	App'd:	XXX	Title CABLE ASSEMBLY							
	Date: 17	DEC. '24	Revisio	n: 1.4		Unit: mm				

1 = ALSR-100 CABLE, COLOR: BLACK





Sheet 1

Drawing Number:

THIS DRAWING IS CONFIDENTIAL AND MUST NOT BE COPIED OR DISCLOSED WITHOUT WRITTEN CONSENT

Drawing © E and O E

CAB613RF

of 1

## **Disclaimer**

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Texim Europe B.V. its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Texim"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Texim makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product.

It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application.

Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time.

All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts.

Please contact us if you have any questions about the contents of the datasheet.

This may not be the latest version of the datasheet. Please check with us if a later version is available.

# Distributed by www.texim-europe.com



# Texim Europe - contact details



### Headquarters & Warehouse

Elektrostraat 17 NL-7483 PG Haaksbergen The Netherlands

T-

+31 (0)53 573 33 33 info@texim-europe.com www.texim-europe.com









### The Netherlands

Elektrostraat 17 NL-7483 PG Haaksbergen

T: +31 (0)53 573 33 33 E: nl@texim-europe.com



### **Belgium**

Zuiderlaan 14, box 10 B-1731 Zellik

T: +32 (0)2 462 01 00 E: belgium@texim-europe.com



### **UK & Ireland**

St Mary's House, Church Lane Carlton Le Moorland Lincoln LN5 9HS

T: +44 (0)1522 789 555 E: uk@texim-europe.com



### Germany - North

Bahnhofstrasse 92 D-25451 Quickborn

T: +49 (0)4106 627 07-0 E: germany@texim-europe.com



### Germany - South

Martin-Kollar-Strasse 9 D-81829 München

T: +49 (0)89 436 086-0 E: muenchen@texim-europe.com



### Austria

Warwitzstrasse 9 A-5020 Salzburg

T: +43 (0)662 216 026 E: austria@texim-europe.com



### Nordic

Stockholmsgade 45 2100 Copenhagen

T: +45 88 20 26 30 E: nordic@texim-europe.com



### Italy

Martin-Kollar-Strasse 9 D-81829 München

T: +49 (0)89 436 086-0 E: italy@texim-europe.com