



Easy Pack S

3.7 V | 660 mAh nominal | 2.5 Wh | 56455 701 014 (SoC 30%)

VARTA Storage GmbH - Rev No. 1- 0225

Distributed by:



WW = calendar week | YY = year

ELECTRICAL SPECIFICATION

Nominal voltage	3.7 V
Rated capacity at (0.5 C / 0.2 C), 23 °C ± 5 °C	630 mAh min., 660 mAh nominal
Watt-hour rating	2.5 Wh
Charging method	Constant Current + Constant Voltage
Max. charge voltage	4.2 V (± 0.05 V)
Max. continuous charge current	630 mA
Rec. charge cut off	By current 6.3 mA or timer 3.5 h
Max. continuous discharge current	1,260 mA (limited by cell)
Rec. discharge cut off	3 V
Internal impedance	Approx. 115 mΩ
Exp. cycle life at (1.0 C / 1.0 C), 23 °C ± 5 °C	≥ 500 cycles ≥ 70 %

GENERAL

(Battery with safety circuit and plastic housing)

Cell	LPP 443441 S
PCM	Yes
NTC	10 kΩ ± 1 %; B-value 3,435 K ± 1 %
ID	3.9 kΩ ± 1 %
Configuration	1S
Weight	Approx. 15 g

CELL&BATTERY PROTECTION

Overcharge detection	4.28 V ± 0.04 V (50 to 150msec. delay, resume 4.28 V ± 0.05 V)
Overdischarge detection	2.50 V ± 0.08 V (10 to 40msec. delay, resume 2.50 ± 0.08 @charging)
Overcurrent detection	3.0 A to 6.9 A (5 to 15msec. delay)


ENVIROMENTAL CONDITIONS

Charge	0 °C to +45 °C
Discharge	-10 °C to +60 °C
Storage	1 month at -20 °C to +60 °C ≥ 80 % 3 months at -20 °C to +45 °C ≥ 80 % 1 year at -20 °C to +30 °C ≥ 80 %
Humidity	0 to 85 RH %

SAFETY CERTIFICATIONS

Please follow VARTA handling and safety precautions for Lilon & LiPolymer. The cell used is a UL recognized component according to UL1642 and IEC 62133-2. The battery meets the requirements of battery directives and the battery part: are RoHS-compliant. The battery is UL 2054 listed and certified according to IEC6321 33-2 and UN38.3

Minimum order quantity: 784 pcs / Order multiples: 196 pcs - Product for OEM customers only!



Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Texim Europe B.V. its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Texim"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Texim makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product.

It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application.

Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time.

All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts.

Please contact us if you have any questions about the contents of the datasheet.

This may not be the latest version of the datasheet. Please check with us if a later version is available.





Headquarters & Warehouse

Elektrostraat 17
NL-7483 PG Haaksbergen
The Netherlands

T: +31 (0)53 573 33 33
E: info@texim-europe.com
Homepage: www.texim-europe.com



The Netherlands

Elektrostraat 17
NL-7483 PG Haaksbergen

T: +31 (0)53 573 33 33
E: nl@texim-europe.com



Belgium

Zuiderlaan 14, box 10
B-1731 Zellik

T: +32 (0)2 462 01 00
E: belgium@texim-europe.com



UK & Ireland

St Mary's House, Church Lane
Carlton Le Moorland
Lincoln LN5 9HS

T: +44 (0)1522 789 555
E: uk@texim-europe.com



Germany

Bahnhofstrasse 92
D-25451 Quickborn

T: +49 (0)4106 627 07-0
E: germany@texim-europe.com



Germany

Martin-Kollar-Strasse 9
D-81829 München

T: +49 (0)89 436 086-0
E: muenchen@texim-europe.com



Austria

Warwitzstrasse 9
A-5020 Salzburg

T: +43 (0)662 216 026
E: austria@texim-europe.com



Nordic

Stockholmsgade 45
2100 Copenhagen

T: +45 88 20 26 30
E: nordic@texim-europe.com



Italy

Martin-Kollar-Strasse 9
D-81829 München

T: +49 (0)89 436 086-0
E: italy@texim-europe.com