


1/LPP 523450 S PCM W

3.7 V | 1,000 mAh nominal | 3.7 Wh | VKB: 56457 201 020 (SoC 30%)

VARTA Storage GmbH - Rev No. 1- 0325





VARTA Storage GmbH 1/LPP 523450 S PCM W VKB: 56457 201 020 11CP6/35/51 3.7V 1000mAh / 3,7Wh WWYYY

VARTA Storage GmbH Nümberger Straße 65 86720 Nördlingen Germany

Assembled in Indonesia

WW = Calendar Week | YY = Year

ELECTRICAL SPECIFICATION

Nominal voltage

Rated capacity at (0.5 C / 0.2 C), 23

°C ± 5 °C

Watt-hour rating

Charging method

Max. charge voltage

Max. continuous charge current

Rec. charge cut off

Max. continuous discharge current

Rec. discharge cut

off

Internal impedance

Exp. cycle life at (1.0 C / 1.0 C), 23 °C ± 5 °C

10

3.7 V

950 mAh min.. 1000 mAh nominal

3.7 Wh

Constant Current + Constant

Voltage

4.2 V (± 0.05 V)

1000 mA (limited by cell)

10 mA or timer 3.5 h

2,000 mA (limited by PCM)

3 V

Approx. 100 mΩ

≥ 500 cycles ≥ 80 %



GENERAL

(Battery pack with safety circuit and wires)

Wire AWG24 UL1007 (red wire (+), white

wire (NTC), black wire (-))

Cell LPP 523450 S

PCM Yes

NTC 10 k Ω ± 1%; B-value 3,380 K

ID None Configuration 1S

Weight Approx. 20 g

CELL&BATTERY PROTECTION

Overcharge detection 4.275 V \pm 0.025 V (0.7 sec. to 1.3 sec. delay, release 4.275 V \pm 0.025 V)

Overdischarge detection 2.3 V \pm 0.058 V (14 msec. to 26 msec. delay, resume 2.3 V \pm 0.058 V)

Overcurrent 2.0 A to 4.0 A (8 msec. to 16 msec.

detection delay)

ENVIROMENTAL CONDITIONS

Charge $0 \, ^{\circ}\text{C to} + 45 \, ^{\circ}\text{C}$ Discharge $-20 \, ^{\circ}\text{C to} + 60 \, ^{\circ}\text{C}$

Storage 1 month at -20°C

1 month at -20°C to +60°C ≥ 80 % 3 months at -20°C to +45°C ≥ 80 % 1 year at -20°C to +30°C ≥ 80 %

Humidity 0 to 85 RH %

SAFETY CERTIFICATIONS

Please follow VARTA handling and safety precautions for Lilon & LiPolymer.

The cell used is a UL recognized component according to UL1642 and IEC 621332. The battery meets the requirements of battery directives and the battery parts are RoHS-compliant. The battery is certified according to IEC6321 33-2 and UN38.3

Minimum order quantity: 600 pcs / Order multiples: 120 pcs - Product for OEM customers only!

Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Texim Europe B.V. its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Texim"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Texim makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product.

It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application.

Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time.

All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts.

Please contact us if you have any questions about the contents of the datasheet.

This may not be the latest version of the datasheet. Please check with us if a later version is available.



Texim Europe - contact details



Headquarters & Warehouse

Elektrostraat 17 NL-7483 PG Haaksbergen The Netherlands

T: +31 (0)53 573 33 33 E: info@texim-europe.com Homepage: www.texim-europe.com







The Netherlands

Elektrostraat 17 NL-7483 PG Haaksbergen

T: +31 (0)53 573 33 33 E: nl@texim-europe.com



Belgium

Zuiderlaan 14, box 10 B-1731 Zellik

T: +32 (0)2 462 01 00 E: belgium@texim-europe.com



UK & Ireland

St Mary's House, Church Lane Carlton Le Moorland Lincoln LN5 9HS

T: +44 (0)1522 789 555 E: uk@texim-europe.com



Germany

Bahnhofstrasse 92 D-25451 Quickborn

T: +49 (0)4106 627 07-0 E: germany@texim-europe.com



Germany

Martin-Kollar-Strasse 9 D-81829 München

T: +49 (0)89 436 086-0 E: muenchen@texim-europe.com



Austria

Warwitzstrasse 9 A-5020 Salzburg

T: +43 (0)662 216 026 E: austria@texim-europe.com



Nordic

Stockholmsgade 45 2100 Copenhagen

T: +45 88 20 26 30 E: nordic@texim-europe.com



Italy

Martin-Kollar-Strasse 9 D-81829 München

T: +49 (0)89 436 086-0 E: italy@texim-europe.com