



SRG-IMX8PL

Standard RISC Gateway with ARM i.MX8M Plus Quad-Core Cortex-A53 1.6GHz Processor

Front View



Rear View



Phoenix Connector



Installation Scenario



DIN-Rail Mount Illustration

Wallmount Illustration

Features

- ARM NXP i.MX8M Plus Quad-Core, Cortex-A53 1.6GHz
- LPDDR4, up to 4 GB, eMMC 5.1 x 1
- HDMI 2.0 x 1
- GbE x 2
- USB 3.0 Gen 1 x 2
- M.2 2230 E Key x 1, Full-sized minicard x 1
- COM x 2, CAN x 2, TPM 2.0



Specifications

System	
Processor	ARM NXP i.MX8M Plus Quad-Core Cortex-A53 1.6GHz Processor (Default w/NPU, optional w/o NPU)
Memory	Onboard LPDDR4 up to 4GB (8GB by request)
Storage	eMMC 5.1 16/32GB (Optional 64/128 GB) Micro SD Card slot x 1
Real Time Clock	RTC x 1, with 3V CR2032H Lithium battery
Security	TPM 2.0 (optional)
Indicators	Programmable LED control x 3
Cellular	Full Size Mini Card x 1 (USB signal)
Wireless Lan	M.2 2230 E-key x 1 (USB, PCIe)
Operating System	Debian 11 (Default, GUI is optional) Android 13 Yocto 4.0
Support Protocol	Modbus, MQTT, OPCUA
I/O Interfaces	
Serial Port	RS-232/422/485 switchable x 2, Phoenix Connector
Ethernet	Gigabit Ethernet x 2, RJ-45 support IEEE 1588, TSN, integrated RGMII
Audio	Line Out x 1 (optional)
USB	USB 3.0 Type-A x 2
ADC	—
DI/DO	—
CAN Bus	CAN-FD x 2 CH, Phoenix Connector
Display	HDMI 2.0 x 1
Power Connector	2 Pin 3.81mm Pitch Phoenix Connector
Debug Port	Micro USB x 1
Expansion Slot	M.2 2230 E-key x 1, support Wifi/BT module Full Size Mini Card x 1, support 4G module, etc) Power control available by software Nano SIM card slot x 1 (optional)
Other Interface	—
Power Supply	
Power Requirement	DC 9-36V (Optional: 12V)
Power Consumption	14.8W (Full Loading)
MTBF (Hours)	1,699,754 Hours
Environmental and Mechanical	
Dimension	4.25" x 3.12" x 1.69" (108mm x 79.5mm x 43mm)
Weight	1.01 lbs (0.46kg)
Mount Options	Wall Mount, Din Rail (Optional)
Operation Temperature	-40 °F ~ 176 °F (-40 °C ~ 80 °C), IEC60068-2 with 0.7 m/s AirFlow, with wide temperature Memory/Storage
Storage Temperature	-40 °F ~ 176 °F (-40 °C ~ 80 °C)
Operation Humidity	0% ~ 90% relative humidity, non-condensing
Certification	CE/FCC Class A


Packing List

- SRG-IMX8PL x 1
- 2pin 3.81mm Power Terminal block w/lock AWG 28~14 x 1
- 18pin 2.54mm Phoenix plug in Connector/lock AWG 30~20 x 1



Dimension

Unit: mm



Optional Accessories

Part Number	Description
9741EG25G0	PCIe mini card, 4G LTE, module kit, Global Band W/ SIM holder, W/Cable & antenna. Quectel, EG25-G
9651882200	M.2 2230 E key Wireless Kit, 802.11 ac/a/b/g/n + BT 5.0, 2T2R, Enli RTL-8822CE, w/2 sets of cable and antenna
9651885201	(M.2 2230 WiFi 6 Kit, 802.11 ax/ac/a/b/g/n + BT, 5.2, Enli ENL-8852BE, w/2 sets of cable(25cm) for Android)
9651PX8L00	AC/DC Adapter, 100V-240V, 12VDC, 40W, 3.34A (for sample order), w/packaging box
125530040D	Power Adapter, DC, 100-240V, 12V, 3.34A, 40W, 3P Phoenix P=3.81mm.
170203180J	POWER CORD, 3P-250V 13A, 1.8M, UK
170X000799	POWER CORD, 3P-125V 10A, 1.8M, USA
170X000800	POWER CORD, 3P-250V 10A, 1.8M, EU
170X000806	POWER CORD, 3P-125V 7A, 1.8M, TWN
170X000803	POWER CORD, 3P-125V 7A, 1.8M, JPN
9651IMX804	Wall mount kit, 75x27mm
9651IMX803	DIN rail kit, 25mm

Ordering Information

Part Number	CPU	NPU	Memory	Display	Storage	LAN	USB	COM	Expansion Slot	Power	Operating Temp	Audio	Others	OS
SRG-IMX8PL-A10-0001	ARM NXP i.MX8M Plus Quad-Core Cortex-A53 1.6GHz Processor	2.3 TOPs	Onboard LPDDR4 2GB	HDMI x 1	eMMC 16GB MicroSD x1	GbE x 2	USB 3.0 Gen1 x 2	RS232(4-wire)/422/485 x 2	M.2 2230 E-key x 1 miniCard (Full) x 1	+12V (Lockable terminal block)	-40°C ~ 80°C	—	CAN 2.0 FD x 2	Debian 11
SRG-IMX8PL-A10-0002	ARM NXP i.MX8M Plus Quad-Core Cortex-A53 1.6GHz Processor	2.3 TOPs	Onboard LPDDR4 4GB	HDMI x 1	eMMC 32GB MicroSD x1	GbE x 2	USB 3.0 Gen1 x 2	RS232(4-wire)/422/485 x 2	M.2 2230 E-key x 1 miniCard (Full) x 1	+ 9 ~ 36 V (Lockable terminal block)	-40°C ~ 80°C	—	TPM x 1 CAN 2.0 FD x 2	Debian 11

Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Texim Europe B.V. its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Texim"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Texim makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product.


It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application.

Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time.

All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts.

Please contact us if you have any questions about the contents of the datasheet.

This may not be the latest version of the datasheet. Please check with us if a later version is available.





Headquarters & Warehouse

Elektrostraat 17
 NL-7483 PG Haaksbergen
 The Netherlands

T: +31 (0)53 573 33 33
 E: info@texim-europe.com
 Homepage: www.texim-europe.com



The Netherlands

Elektrostraat 17
 NL-7483 PG Haaksbergen

T: +31 (0)53 573 33 33
 E: nl@texim-europe.com



Belgium

Zuiderlaan 14, box 10
 B-1731 Zellik

T: +32 (0)2 462 01 00
 E: belgium@texim-europe.com



UK & Ireland

St Mary's House, Church Lane
 Carlton Le Moorland
 Lincoln LN5 9HS

T: +44 (0)1522 789 555
 E: uk@texim-europe.com



Germany

Bahnhofstrasse 92
 D-25451 Quickborn

T: +49 (0)4106 627 07-0
 E: germany@texim-europe.com



Germany

Martin-Kollar-Strasse 9
 D-81829 München

T: +49 (0)89 436 086-0
 E: muenchen@texim-europe.com



Austria

Warwitzstrasse 9
 A-5020 Salzburg

T: +43 (0)662 216 026
 E: austria@texim-europe.com



Nordic

Stockholmsgade 45
 2100 Copenhagen

T: +45 88 20 26 30
 E: nordic@texim-europe.com



Italy

Martin-Kollar-Strasse 9
 D-81829 München

T: +49 (0)89 436 086-0
 E: italy@texim-europe.com