


GENESYSM-TGU6

GENE System with 11th Generation Intel® Core™ i7/i5/i3/Celeron Processor



Features

- 11th Gen Intel® Core™ i7/i5/i3/Celeron Processor
- DDR4 SODIMM x 2, up to 64GB
- DP 1.4a x 2, HDMI 2.0b x 1, Type C DP x 1
- 2.5GbE x 1, GbE x 1, SATA III x 1
- USB 3.2 Gen2 x 4, USB 2.0 x 2, USB Type C x 1
- M.2 2280 M key x 1, M.2 2230 E key x 1, Full size mSATA/mPCIe x 1
- Wide DC Input 9-36V
- Line-in/Line-out/MIC (Optional)



USB	USB3.2 Gen 2 x 4 USB3.2 Gen 2 Type C x 1 (PD 5V/3A) USB2.0 x 2
Serial Port	COM1 (RS232/422/485) COM2 (RS232/422/485, supports 5V/12V/RI)
Video	HDMI 2.0b x 1, DP1.4 x 2, Type-C DP1.4 x 1
Internal I/O	
USB	—
Serial Port	—
Video	—
SATA	SATA III x 1 +5V SATA Power Connector x 1
Audio	Audio Header x 1
DIO/GPIO	—
SMBus/I2C	SMBus/I2C x1(Default: SMBus)
Touch	—
Fan	4pins Smart Fan x 1
Sim	Nano SIM x 1
Front Panel	HDD LED, PWR LED, Power Button, Buzzer, Reset
Others	—
Expansion	
Mini PCIe/mSATA	Full-Sized mSATA/mPCIe x 1 (default: mSATA, select with BIOS)
M.2	M-Key 2280 x 1 (PCIex4) E-Key 2230 x 1 (PCIe, USB2.0)
Others	—
Environment & Certification	
Operating Temp.	32°F ~ 122°F (0°C ~ 50°C)
Storage Temp.	-40°F ~ 185°F (-40°C ~ 85°C)
Operating Humidity	0% ~ 90% relative humidity, non-condensing
MTBF (Hours)	329,884
EMC	CE/FCC Class A

Specifications

System	
Form Factor	3.5" SubCompact Board System
CPU	Intel® 11th Generation Core™/Celeron CPU i7-1185G7E (4C/8T, 1.80GHz, up to 4.40GHz, TDP-up 28W) i5-1145G7E (4C/8T, 1.50GHz, up to 4.10GHz, TDP-up 28W) i3-1115G4E (2C/4T, 2.20GHz, up to 3.90GHz, TDP-up 28W) Celeron® 6305E (2C/2T, 1.80GHz, TDP 15W)
Chipset	Integrated with Intel® SoC
Memory Type	DDR4 up to 3200MHz, Dual Channel SODIMM x 2, up to 64GB, Support IB ECC(select SKUs)
BIOS	UEFI
Wake on LAN	Yes
Watchdog Timer	255 Levels
Security	TPM2.0
RTC Battery	Lithium Battery 3V/240mAh
Dimensions	7.00" x 5.28" x 1.97" (178.0mm x 134.1mm x 50.0mm)
OS Support	Windows 10 (64bit) Linux Ubuntu 20.04.3(IOT)/Kernel 5.13
Power	
Power Requirement	+9-36V (Optional: +12V)
Power Supply Type	ATX
Connector	DC Jack Connector
Power Consumption	Intel® i7-1185G7E, DDR4 3200MHz 32GB x 2, 4.96A@ +12V(TYPICAL) Intel® i7-1185G7E, DDR4 3200MHz 32GB x 2, 7.32A@ +12V(MAX)
Display	
Controller	Intel® Iris® Xe Graphics Intel® UHD Graphics
LVDS/eDP	—
Display Interface	HDMI 2.0b x 1 DP1.4 x 2 Type-C DP1.4 x 1
Multiple Display	Up to 4 Simultaneous Displays
Audio	
Codec	Realtek ALC897/892
Audio Interface	Line-in/Line-out/MIC (Optional)
Speaker	—
External I/O	
Ethernet	Intel® i219, 10/100/1000Base, RJ-45 x 1 Intel® i225/i226, 10/100/2500Base, RJ-45 x 1


Packing List

Part Number	Description	QTY
GENESYSM-TGU6	GENESYSM-TGU6 GENE System	1


Optional Accessories

Part Number	Description	QTY
1702031802	Power Cord (US Type)	1
1702031803	Power Cord (Europe Type)	1
170203180E	Power Cord (Japan)	1
170X000517	Audio cable	1
1255X00063	Power Adapter 12V/12.5A 150W w/Lock 180D.DELTA.DPS150AB-15 J	1
GENESYSM-TGU6-HDD1	HDD Kit. For GENESYSM-TGU6	1
GENESYSM-ALL-VESA1	VESA Mount Kit. For GENESYSM-TGU6	1
GENESYSM-ALL-WMT1	Wall Mount Kit. For GENESYSM-TGU6	1

Note: All specifications are subject to change without notice.

Block Diagram**Dimension**

Unit: mm

**Ordering Information**

Part number	CPU	Fan/Fanless	Display	LAN	USB	RS-232/422/485	Storage	Expansion slot	TPM	Power	Operating Temp	Others
GENESYSM-TGU6-A10-0001	i7-1185G7E	Cooler	DP x 2, TypeC DP x 1 HDMI x 1	GbE x 1 2.5GbE x 1	USB 3.2 Gen 2 x 4 USB 3.2 Gen2 TypeC x 1 USB 2.0 x 2	2	SATA x 1 mSATA (Full size)x 1	M.2 M Key 2280 x 1 M.2 E Key 2230 x 1	2.0	9~36V	0~50°C	nano SIM
GENESYSM-TGU6-A10-0002	i5-1145G7E	Cooler	DP x 2, TypeC DP x 1 HDMI x 1	GbE x 1 2.5GbE x 1	USB 3.2 Gen 2 x 4 USB 3.2 Gen2 TypeC x 1 USB 2.0 x 2	2	SATA x 1 mSATA (Full size)x 1	M.2 M Key 2280 x 1 M.2 E Key 2230 x 1	2.0	9~36V	0~50°C	nano SIM
GENESYSM-TGU6-A10-0003	i3-1115G4E	Cooler	DP x 2, TypeC DP x 1 HDMI x 1	GbE x 1 2.5GbE x 1	USB 3.2 Gen 2 x 4 USB 3.2 Gen2 TypeC x 1 USB 2.0 x 2	2	SATA x 1 mSATA (Full size)x 1	M.2 M Key 2280 x 1 M.2 E Key 2230 x 1	2.0	9~36V	0~50°C	nano SIM
GENESYSM-TGU6-A10-0004	Celeron® 6305E	Cooler	DP x 2, TypeC DP x 1 HDMI x 1	GbE x 1 2.5GbE x 1	USB 3.2 Gen 2 x 4 USB 3.2 Gen2 TypeC x 1 USB 2.0 x 2	2	SATA x 1 mSATA (Full size)x 1	M.2 M Key 2280 x 1 M.2 E Key 2230 x 1	2.0	9~36V	0~50°C	nano SIM

Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Texim Europe B.V. its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Texim"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Texim makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product.

It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application.

Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time.

All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts.

Please contact us if you have any questions about the contents of the datasheet.

This may not be the latest version of the datasheet. Please check with us if a later version is available.





Headquarters & Warehouse

Elektrostraat 17
NL-7483 PG Haaksbergen
The Netherlands

T: +31 (0)53 573 33 33
E: info@texim-europe.com
Homepage: www.texim-europe.com



The Netherlands

Elektrostraat 17
NL-7483 PG Haaksbergen

T: +31 (0)53 573 33 33
E: nl@texim-europe.com



Belgium

Zuiderlaan 14, box 10
B-1731 Zellik

T: +32 (0)2 462 01 00
E: belgium@texim-europe.com



UK & Ireland

St Mary's House, Church Lane
Carlton Le Moorland
Lincoln LN5 9HS

T: +44 (0)1522 789 555
E: uk@texim-europe.com



Germany

Bahnhofstrasse 92
D-25451 Quickborn

T: +49 (0)4106 627 07-0
E: germany@texim-europe.com



Germany

Martin-Kollar-Strasse 9
D-81829 München

T: +49 (0)89 436 086-0
E: muenchen@texim-europe.com



Austria

Martin-Kollar-Strasse 9
D-81829 München

T: +49 (0)89 436 086-0
E: austria@texim-europe.com



Nordic

Stockholmsgade 45
2100 Copenhagen

T: +45 88 20 26 30
E: nordic@texim-europe.com



Italy

Martin-Kollar-Strasse 9
D-81829 München

T: +49 (0)89 436 086-0
E: italy@texim-europe.com