


PICO-APL2

Pico-ITX Board with Intel Atom® E3900 series/ Pentium® N4200/ Celeron® N3350 Processor SoC



Specifications

System	
Form Factor	PICO-ITX
CPU	Intel® Atom® / Celeron® / Pentium® Processors: N3350 (2C/2T, 1.10GHz, 6W) N4200 (4C/4T, 1.10GHz, 6W) E3950 (4C/4T, 1.60GHz, 12W)
Chipset	Integrated with Intel® SoC
Memory Type	DDR3L 1866, Single Channel SODIMM x 1, Non-ECC (Max.8GB, up to 1600MHz)
BIOS	UEFI
Wake on LAN	Yes
Watchdog Timer	255 Levels
Security	—
RTC Battery	Lithium Battery 3V/240mAh
Dimension	3.94" x 2.84" (100mm x 72mm)
Gross Weight	0.18 lbs (0.08 kg)
OS Support	Windows 10 (64 bit) Linux Ubuntu 20.04.4/ Kernel 5.11.0-30-generic
Power	
Power Requirement	+12V
Power Supply Type	AT/ATX
Connector	Line-Out (Audio function not available for WiTAS SKU)
Power Consumption	Intel® N4200, DDR3L 8GB x 1, 2.16A@ +12V(TYPICAL) Intel® N4200, DDR3L 8GB x 1, 2.28A@ +12V(MAX)
Display	
Controller	Intel® HD Graphics 500/505
LVDS/eDP	LVDS x 1 (18/24bit 2CH) 1920 x 1200 @60Hz
Display Interface	HDMI 1.4 x 1, 3840 x 2160 @30Hz DDI (Via BIO, Optional)
Multiple Display	Up to 3 Simultaneous Displays
Audio	
Codec	Realtek ALC897/888
Audio Interface	Line-Out (Audio function not available for WiTAS SKU)
Speaker	—
External I/O	
Ethernet	Intel® i210 1GbE, RJ45 x 1
USB	USB 3.2 Gen1 x 2
Serial Port	—
Video	HDMI 1.4 x 1
Internal I/O	
USB	USB 2.0 x 1

Features

- Intel Atom® E3900/ Pentium® N4200/ Celeron® N3350 Processor SoC
- DDR3L 1866, Single Channel SODIMM x 1, Non-ECC (Max.8GB, up to 1600MHz)
- 18/24-bit Dual Channel LVDS LCD
- HDMI1.4 x 1, Pin header (up to 2K @30Hz)
- SATA 6.0Gb/s x 1, mSATA (Full Size) x 1
- Intel® i210AT/i210IT, 10/100/1000Base x 1 (Pin header) *LED in separated pin header
- USB 3.2 Gen 1 x 2, USB 2.0 x 1
- RS-232 x 1, RS-232/422/485 x 1
- Mini-Card x 1 (Half-Size, PCIe/USB)
- SMBus/I2C x 1 (default SMBus)
- Digital I/O 4-bit
- BIO Connector for Daughter Board (Optional)



Serial Port	COM1 (RS232) COM2 (RS232/422/485, support 5V/12V/RI)
Video	LVDS x 1
SATA	SATA 6.0 Gb/s x 1, +5V SATA Power Connector x 1
Audio	Line-out header x 1 (Audio function not available for WiTAS SKU)
DIO/GPIO	GPIO 4-bit
SMBus/I2C	I2C/SMBus x1 (Default: SMBus)
Fan	—
Front Panel	HDD LED, PWR LED, Power Button, Buzzer, Reset
Others	—
Expansion	
Mini PCIe/mSATA	Full-Size mSATA/mPCIe x 1 (Default: mSATA, select with HW BOM) Half-Sized mPCIe x 1
M.2	—
Others	BIO x 1 (Optional, supports PCIe [x1] x 2, line out, DDI, GPIO, LPC, SMBUS, USB 3.0/2.0)
Environment & Certification	
Operating Temp	32°F ~ 140°F (0°C ~ 60°C)
Storage Temp	-40°F ~ 185°F (-40°C ~ 85°C)
Operating Humidity	0% ~ 90% relative humidity, non-condensing
MTBF (Hours)	525,137
EMC	CE/FCC Class A

Packing List


- PICO-APL2

Optional Accessories

Part Number	Description	Qty.
1709070500	SATA CABLE.500mm	1
1702150155	SATA Power Cable.150mm	1
1700050207	USB Cable.200mm.for PFM-945C Active Others	1
1703200153	COM Port 1/2 & line out cable.2ports.150mm	1
PICO-APL1-HSP01	Heatspreader.100*72*8.5mm.Silver.for Pentium N4200/ Celeron N3350 of PICO-APL2	1
PICO-APL1-HSP02	Heat spreader.100*72*8.5mm for Atom E39XX series of PICO-APL2	1
PICO-APL1-HSK02	Heat Sink.100*72*15.5mm.Silver.used with HSP	1
PER-P30D-A10	120W, DC-DC Converter, 9~36V input, 12V output, Rev A1.0, 30 x 72mm	1


Note: All specifications are subject to change without notice.

Block Diagram



Dimension

Unit: mm



Ordering Information

Part number	CPU	Memory	Display	Storage	LAN	USB	RS-232/422/485	Expansion slot	Power	Operating Temp	Others
PICO-APL2-A10-0001	N4200	DDR3L	HDMI x 1 LVDS x 1	SATAIII x 1	GbE x 1	USB3.2 Gen 1 x 2 USB2.0 x 1	2	Full-size mSATA/mPCIe or USB2.0 x 1 Half-size Mini Card x 1	+12V	0°C ~ 60°C	DIO 4 bit SMBus
PICO-APL2-A10-0002	N3350	DDR3L	HDMI x 1 LVDS x 1	SATAIII x 1	GbE x 1	USB3.2 Gen 1 x 2 USB2.0 x 1	2	Full-size mSATA/mPCIe or USB2.0 x 1 Half-size Mini Card x 1	+12V	0°C ~ 60°C	DIO 4 bit SMBus
PICO-APL2-A10-0003	E3950	DDR3L	HDMI x 1 LVDS x 1	SATAIII x 1	GbE x 1	USB3.2 Gen 1 x 2 USB2.0 x 1	2	Full-size mSATA/mPCIe or USB2.0 x 1 Half-size Mini Card x 1	+12V	0°C ~ 60°C	DIO 4 bit SMBus

Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Texim Europe B.V. its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Texim"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Texim makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product.

It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application.

Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time.

All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts.

Please contact us if you have any questions about the contents of the datasheet.

This may not be the latest version of the datasheet. Please check with us if a later version is available.





Headquarters & Warehouse

Elektrostraat 17
NL-7483 PG Haaksbergen
The Netherlands

T: +31 (0)53 573 33 33
E: info@texim-europe.com
Homepage: www.texim-europe.com



The Netherlands

Elektrostraat 17
NL-7483 PG Haaksbergen

T: +31 (0)53 573 33 33
E: nl@texim-europe.com



Belgium

Zuiderlaan 14, box 10
B-1731 Zellik

T: +32 (0)2 462 01 00
E: belgium@texim-europe.com



UK & Ireland

St Mary's House, Church Lane
Carlton Le Moorland
Lincoln LN5 9HS

T: +44 (0)1522 789 555
E: uk@texim-europe.com



Germany

Bahnhofstrasse 92
D-25451 Quickborn

T: +49 (0)4106 627 07-0
E: germany@texim-europe.com



Germany

Martin-Kollar-Strasse 9
D-81829 München

T: +49 (0)89 436 086-0
E: muenchen@texim-europe.com



Austria

Martin-Kollar-Strasse 9
D-81829 München

T: +49 (0)89 436 086-0
E: austria@texim-europe.com



Nordic

Stockholmsgade 45
2100 Copenhagen

T: +45 88 20 26 30
E: nordic@texim-europe.com



Italy

Martin-Kollar-Strasse 9
D-81829 München

T: +49 (0)89 436 086-0
E: italy@texim-europe.com