


NIKY-2155-NX

15.6" Full HD 1920 x 1080 AI Panel PC with NVIDIA® Jetson Orin™ NX

Front View



Top View



Bottom View



Features

- 15.6" FHD 1920x1080
- PCAP Touch
- NVIDIA® Jetson Orin™ NX
- 8GB LPDDR5
- M.2 E-Key x 1, M.2 B-Key x 1, M.2 M-Key x 1
- CANBus, DIO, COM Port
- GbE LAN x 2
- DC 12~24V



Giga LAN



USB 3.2 Gen2



Full-Size M.2 Card



Wide Voltage




Specifications

System	
Processor	NVIDIA® Jetson Orin™ NX 6-core Arm® Cortex®-A78AE v8.2 64-bit CPU
System Memory	8GB LPDDR5
LCD/CRT controller	—
Ethernet	GbE LAN x 2
I/O Port	USB 3.2 Gen 2 (Type-A) x 4 GbE LAN x 2 Micro USB x 1 for OS Flash DB-9 x 1 for CANBus DB-9 x 1 for RS-232/422/485 DB-15 x 1 for 8-bit DIO Power ON/OFF Switch x 1 Recovery Button x 1 Antenna Hole x 6
Storage Disk Drive	M.2 2280 M-Key x 1 for Storage (Default: 128GB)
Expansion Slot	M.2 2230 E-Key x 1 M.2 3042/3052 B-Key x 1
OS support	Ubuntu 22.04
Mechanical	
Construction	Aluminum Front Bezel + Metal Chassis
Mounting	VESA 100 / Panel Mount
Dimension	15.2" x 9.3" x 2.6" (385.6mm x 235.0mm x 66.6mm)
Carton Dimension	20.3" x 15.2" x 7.8" (515mm x 385mm x 198mm)
Gross Weight	9.39 lb. (4.26Kg)
Environmental	
Operating Temperature	23°F ~ 131°F (-5°C ~ 55°C) with 0.7 m/s airflow
Storage Temperature	-4°F ~ 140°F (-20°C ~ 60°C)
Storage Humidity	90% @ 40°C, non-condensing
Vibration	1Grms / 5~ 500Hz / operation
Shock	15 G peak acceleration (11 msec. duration)
EMC	CE/FCC Class A
Power Supply	
DC Input	DC 12~24V
LCD	
Display Type	15.6" TFT-LCD, LED
Max Resolution	1920 (H) x 1080 (V)
Max. Colors	16.7M
Luminance	350 cd/m²
Viewing Angle	160° (H) / 160° (V)
Back Light	LED
Back Light MTBF (Hours)	35,000
Touchscreen	
Type	P-CAP
Light Transmission	≥ 85%



Dimension

Unit: mm



Packing List

- Phoenix Power Connector
- Screws
- NIKY-2155-NX

Optional Accessories

Part Number	Description
170X000799	Power Cord (US Type)
170X001024	Power Cord (European Type)
170X000803	Power Cord (Japanese Type)
1255300611	12V 60W Power Adapter

Ordering Information

Part Number	Display Type	Max Resolution	Luminance	View Angle	CPU	LAN	USB	RS-232/422/485	Storage	RAM	Display	Internal Expansion	Mounting	Power	Operating Temp.	Touch
NIKY-2155HTT-NX-A1-1010	15.6" TFT LCD	1920 (H) x 1080 (V)	350 cd/m ²	160° (H) / 160° (V)	NVIDIA® Jetson Orin™ NX	2	USB 3.2 Gen 2 x 4	1	M.2 2280 M-Key x 1 (Default: 128GB)	8GB	—	M.2 2230 E-Key x 1 M.2 3042/3052 B-Key x 1	VESA / Panel Mount	DC 12V ~ 24V	23°F ~ 131°F (-5°C ~ 55°C)	P-CAP

Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Texim Europe B.V. its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Texim"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Texim makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product.

It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application.

Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time.

All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts.

Please contact us if you have any questions about the contents of the datasheet.

This may not be the latest version of the datasheet. Please check with us if a later version is available.





Headquarters & Warehouse

Elektrostraat 17
NL-7483 PG Haaksbergen
The Netherlands

T: +31 (0)53 573 33 33
E: info@texim-europe.com
Homepage: www.texim-europe.com



The Netherlands

Elektrostraat 17
NL-7483 PG Haaksbergen

T: +31 (0)53 573 33 33
E: nl@texim-europe.com



Belgium

Zuiderlaan 14, box 10
B-1731 Zellik

T: +32 (0)2 462 01 00
E: belgium@texim-europe.com



UK & Ireland

St Mary's House, Church Lane
Carlton Le Moorland
Lincoln LN5 9HS

T: +44 (0)1522 789 555
E: uk@texim-europe.com



Germany

Bahnhofstrasse 92
D-25451 Quickborn

T: +49 (0)4106 627 07-0
E: germany@texim-europe.com



Germany

Martin-Kollar-Strasse 9
D-81829 München

T: +49 (0)89 436 086-0
E: muenchen@texim-europe.com



Austria

Martin-Kollar-Strasse 9
D-81829 München

T: +49 (0)89 436 086-0
E: austria@texim-europe.com



Nordic

Stockholmsgade 45
2100 Copenhagen

T: +45 88 20 26 30
E: nordic@texim-europe.com



Italy

Martin-Kollar-Strasse 9
D-81829 München

T: +49 (0)89 436 086-0
E: italy@texim-europe.com